



APPLICABLE STANDARDS:

- ▲ BASIC DESIGN, API 602 & ANSI B16.34
- ▲ SOCKET-WELD (S.W), ANSI B16.11
- ▲ SCREWED END (S.E), ANSI B1.20.1
- ▲ VALVES TEST AND INSPECT: API 598
- ▲ STANDARD MATERIAL: A105.LF2.F5.F11.F22
F304.F304LF316.F316L

Nominal diameter	Reduced Port	mm(in)	8(1/4)	10(3/8)	15(1/2)	20(3/4)	25(1)	32(1¼)	40(1½)	50(2)	—
	Full Port	mm(in)	—	—	10(3/8)	15(1/2)	20(3/4)	25(1)	32(1¼)	40(1½)	50(2)
d		mm	8	10	10	13	17	23	30	37	46
L		mm	79	79	79	92	111	130	152	172	200
H (Open)		mm	176	176	176	176	212	230	254	294	327
W		mm	100	100	100	100	125	160	160	180	200
Weight	B.B	kg	2.2	2.1	1.9	2.1	3.9	5.8	7.2	10.8	16
	W.B	kg	1.9	1.8	1.7	2.1	3.7	5.2	6.2	10.4	14.8

Due to continuous development of our products, we reserve the right to modify our product design or construction without prior notice.