



APPLICABLE STANDARDS:

- ▲ BASIC DESIGN, API 602 & ANSI B16.34
- ▲ SOCKET-WELD (S.W), ANSI B16.11
- ▲ SCREWED END (S.E), ANSI B1.20.1
- ▲ VALVES TEST AND INSPECT: API 598
- ▲ STANDARD MATERIAL: A105.LF2.F5.F11L.F22
F304.F304L.F316.F316L

DIMENSIONS

Nominal diameter		mm(in)	10(3/8)	15(1/2)	20(3/4)	25(1)	32(1¼)	40(1½)	50(2)
d	CLASS 800	mm	10	13	17	23	30	37	46.5
	CLASS 1500	mm	10	13	17	23	30	37	46.5
L	CLASS 800	mm	98	98	98	120	140	140	170
	CLASS 1500	mm	102	102	102	130	150	190	190
H	CLASS 800	mm	84	84	84	120	114	114	145
	CLASS 1500	mm	90	90	101	125	132	143	203
Weight	CLASS 800	kg	3.0	2.9	3.7	6.5	8.5	9.6	10.8
	CLASS 1500	kg	3.2	3.2	4.1	7.2	10.5	11.6	12

Due to continuous development of our products, we reserve the right to modify our product design or construction without prior notice.