



APPLICABLE STANDARDS:

- ▲ BASIC DESIGN, API 602 & ANSI B16.34
- ▲ SOCKET-WELD (S.W), ANSI B16.11
SCREWED END (S.E), ANSI B120.1
- ▲ VALVES TEST AND INSPECT: API 598
- ▲ STANDARD MATERIAL: A105.LF2.F5.F11.F22
F304.F304L.F316.F316L

Nominal diameter	Reduced Port	mm(in)	8(1/4)	10(3/8)	15(1/2)	20(3/4)	25(1)	32(1¼)	40(1½)	50(2)	65(2½)	80(3)
	Full Port	mm(in)	—	—	10(3/8)	15(1/2)	20(3/4)	25(1)	32(1¼)	40(1½)	50(2)	—
d	mm	7	7	10	13.6	18	24	29	36.8	46.5	51	
L	mm	79	79	79	92	111	120	120	140	178	185	
H (Open)	mm	166	166	166	169	193	230	246	283	330	359	
W	mm	100	100	100	100	125	160	160	180	200	200	
Weight	B.B	kg	2.3	2.2	2.1	2.3	4.0	5.9	6.9	11.2	15.8	20
	W.B	kg	1.9	1.8	1.7	2.1	3.7	5.2	6.2	10.4	14.8	—

Due to continuous development of our products, we reserve the right to modify our product design or construction without prior notice.