



three-piece body

Type of connection

RF and RTJ flange ends to ANSI B16.5 or API 605
and MSS SP-44 standard.

BW flange ends to ANSI B16.25 standard

Type of operation

Lever

Connection dimensions of Worm Gear actuator.

Electric actuator, Pneumatic actuator to ISO 5211 standard.

Anti-static constructions "AS" and

Fire-resistant constructions "FD".

CLASS 300														
DN	50	65	80	100	150	200	250	300	350	400	450	500	600	700
NPS	2	2 1/2	3	4	6	8	10	12	14	16	18	20	24	28
L(RF)	216	241	283	305	403	502	568	648	762	838	914	991	1143	1346
	8.5	9.5	11.13	12	15.88	19.75	22.38	25.5	30	33	36	39	45	53
L(BW)	216	241	283	305	457	521	559	635	762	838	914	991	1143	1346
	8.5	9.5	11.13	12	18	20.5	22	25	30	33	36	39	45	53
L ₂ (RTJ)	232	257	298	321	419	518	584	664	778	854	930	1010	1165	1372
	9.13	10.13	11.75	12.63	16.5	20.38	23	26.13	30.63	33.63	36.63	39.75	45.89	54
H	153	165	195	213	272	342	495	580	625	720	790	840	1050	1150
	6.02	6.5	7.68	8.39	10.7	13.5	19.5	22.85	24.6	28.35	31	33.1	41.34	45.3
D ₀ (W)	400	400	600	850	1100	1500	*350	*350	*600	*800	*800	*800	*800	*800
	15.74	15.74	23.62	33.46	43.3	59	13.8	13.8	23.6	23.6	31.5	31.5	31.5	31.5
RF(kg)	18	27	47	80	118	200	365	530	740	1030	1320	1540	2600	3900
BW(kg)	14	22	38	65	105	185	342	503	713	1000	1285	1498	2540	3825

* Worm Gear of Electric actuator operated.

MATERIAL LIST

NO.	Part Name	Carbon Steel		Stainless Steel			
		WCB	LCB	CF8	CF8M	CF3	CF3M
1	Body	A216WCB A105	A352LF2	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M
2	L-body	A216WCB A105	A352LCB A350LF2	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M
3	R-body	A216WCB A105	A352LCB A350LF2	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M
4	Ball	A105/Ep.Cr	A182 F304	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M
5	Stem	A182 F6	A182 F6	A182 F304	A182 F316	A182 F304L	A182 F316L
6	Seat	A182 F6	A182 F6	A182 F304	A182 F316	A182 F304L	A182 F316L
7	Seat Ring	PTFE, POM or HF(Co-CrA)					
8	Gasket	PTFE or Flexible Graphite and Stainless Steel					
9	O-Ring	VITON	VITON	VITON	VITON	VITON	VITON
10	Trunnion	A182F6	A182F6	A182F304	A182F316	A182F304L	A182F316L
11	Spring	AISI6150 17-17PH(Inconel for NACE) Ni-Cr Alloy					
12	Drain plug	A182F6	A182F6	A182F304	A182F316	A182F304L	A182F316L
13	Bolt	A193B7 A320L7 A193B8 A193B8M					
14	Stem bearing	PTFE or Stainless Steel and Graphite					
15	Stem seat	PTFE	PTFE	PTFE	PTFE	PTFE	PTFE
16	Small spring	17-17PH(Inconel for NACE) Ni-Cr Alloy					
17	Small ball	A182 F304 A182 F316					
18	Trunnion bearing	PTFE or Stainless Steel and Graphite					
19	Plug	A105	A182 F6	A182 F304	A182 F316	A182 F304L	A182 F316L
20	Spring seat	A105	A182 F6	A182 F304	A182 F316	A182 F304L	A182 F316L
21	Bonnet Bolt	A193 B7 A320 L7 A320 B8 A193 B8M					
22	Bonnet Nut	A194 2H A194 4 A194 8					
23	Pin	Carbon Steel or Alloy Steel					
24	Gland	A182F6	A182F6	A182F304	A182F316	A182F304L	A182F316L
25	Gland flange	A216 WCB	A352LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M
26	Stem packing	PTFE or Flexible Graphite					
27	Bonnet	A216 WCB A105	A352LCB A350LF2	A351CF8	A351CF8M	A351CF3	A351CF3M

The material is according to ASTM standard.